




KAI HE MACHINERY CO., LTD



**Grinding Rack Gear
Professional Manufacturer**



KAI HE MACHINERY

KAI HE is mainly specialized in the production of transmission rack gears. the first ground rack manufacturer in Taiwan , while today it is a certified company (ISO 9001 : 2015), technologically advanced and structured with updated production plants.


Internally HAI HE has highly qualified personnel in order to offer customized answers to the most complex demands of every customer. Today, thanks to the production flexibility and to the industrial automation, KAI HE is able to realize products with high competitive prices in all over the world, both with standard features and with the most elaborate customizations.

With over 15 years of experience in rack manufacturing under their belt and rank among the top five rack manufacturers in Asia, Kai He Machinery Co., Ltd. is also the first Taiwanese company to use all German-made machinery while insisting on only using Taiwan-produced steel.

Kai He stresses the importance of its ten manufacturing processes and is adamant that these processes are the reason that it could provide products of high precision, high rigidity, and great precision, just like those produced by German brands.

Using the latest and most cutting-edge Computer Numerical Control (CNC) milling and grinding machines from Germany, Kai He ensures that the rack tooth surfaces are uniform and of the same quality even when mass produced.

INDEX



Rack & Pinion Terminology	01 - 02
Rack Installation	03
Rack & Pinion Alignment	04
Rack Quality and Applications	05
Structure of Our Item Codes	06
Quality Classes	09 - 16
Helical Rack Series (C45 Q5 ~ Q10)	18 - 23
Straight Rack Series (C45 Q5 ~ Q10)	25 - 30
Installation Gauge	32
Helical Tooth Pinion Series (16CrMo4 Q5)	34
Flanged Helical Pinion Series (16CrMo4 Q5)	35
Helical Tooth Pinion Series (C45 Q10)	36
Straight Tooth Pinion Series (16CrMo4 Q5)	37
Straight Tooth Pinion Series (C45 Q10)	38

Module

The module is the relative size of the rack and pinion as described by the pinion. It is the ratio of the diameter of a gear to the number of teeth on the gear. The module and number of teeth give the reference pitch diameter:

$$\text{Module (M)} = \frac{\text{Pitch Diameter}}{\text{Number of Teeth (z)}}$$


Reference Pitch Diameter = Module (M) x Number of Teeth (z)

The rack and pinion must have the same modules.

Tooth Thickness Tolerance


Tooth Thickness Tolerance is the relationship between tooth thickness and a measuring pin measurement.

- The tooth thickness of racks is usually measured via the pin measurement as tooth thickness can not be measured directly.
- A measuring pin is put into the teeth and measured to the back of the rack.



Pitch Error

Pitch: Distance between teeth as measured from a point on one rack tooth to the corresponding point on the next gear tooth.




Single Pitch Error: Error in the pitch between two teeth relative to the ideal.

Total Pitch Error: Culmulative pitch error over the length of the rack.

Circular Pitch:

The distance from a point on one gear tooth to the corresponding point on the next gear tooth, measured along the pitch circle.




Pitch Circle: A circle transcribing the contact point on the teeth where the rack and pinion mesh correctly.

Pitch Diameter: The diameter of the gear's pitch circle.

Pressure Angle: The angle made by the sides of the tooth as it angles towards the top of the tooth. Mating gears and racks must have the same pressure angle.

Mounting Distance: Distance between the center of the pinion and the bottom of the rack that ensures proper mesh. The mounting distance should stay consistent for the length of the rack.

$$\text{Mounting Distance} = \text{Pitch Height of Rack} + \text{Pitch Radius of Pinion}$$




Helix Angle: Angle of the rack or gear tooth.

Racks and pinions use a common helix angle of 19°31'42"


Rack Installation

These are the three main steps to installing rack. See the Rack Installation Instructions for more detailed installation information. Installation of multiple rack pieces end-to-end requires an opposite tooth installation gauge:


Step 1
Put the racks on the base, end to end, without the screw



Step 2
Put the racks gauge across the ends of the joined racks and adjust the pitch. The ends of the racks each from half a tooth.




Step 3
Bolt the racks to the base in sequence. Install dowel pins.




Rack & Pinion Alignment

For best performance, the rack and pinion must be installed with proper tooth engagement. To check this, we recommed using a red compound and check the gear mesh contact pattern under load conditions.



Correct
Contact is even across the face of the tooth




Not Parallel
The pinion and rack are not parallel. Adjust the pinion so the face of the pinion and the side of the rack are parallel. The axis of the pinion should be perpendicular to the rack.






Incorrect Mounting Distance
There is insufficient tooth contact between the rack and pinion. Adjust the center distance between the rack and the pinion. The pinion specification tables include the center distance for each size pinion.



Quality	Total Pitch Error (µm/1000mm)	Tooth Thickness Tolerance (µm/1000mm)	Applications (Examples)
5	±25	-22	<ul style="list-style-type: none"> High precision machine tools with electrical preload. Machine tools, lifting axis, multiple pinion contact.
6	±35	-36	<ul style="list-style-type: none"> Wood, plastic, composite, aluminium working machines. Machine tools, integratable racks, water cutting machines, tube bending systems, plasma cutting machines, laser cutting machines.
7	±45	-47	<ul style="list-style-type: none"> Wood working machines, Linear axis with high requirement for a smooth running. Robots.
8	±60	-95	<ul style="list-style-type: none"> Portals, handling linear axis. Linear axis.
9	±90	-109	<ul style="list-style-type: none"> Linear axis with low load feed units for adjustment.
10	±200	-109	<ul style="list-style-type: none"> Lifting axis, Handling, welding robots.





Quality Classes	Quality Tolerances	Pitch Error
-----------------	--------------------	-------------

Quality Classes	Quality Tolerances	Pitch Error
-----------------	--------------------	-------------

M1.5 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.005	±0.024
	Q6	-0.020	±0.008	±0.026
	Q7	-0.040	±0.008	±0.034
	Q8	-0.066	±0.015	±0.060
	Q9	-0.080	±0.020	±0.080
	Q10	-0.120	±0.034	±0.140

M2 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.005	±0.020
	Q6	-0.020	±0.008	±0.026
	Q7	-0.040	±0.008	±0.034
	Q8	-0.066	±0.016	±0.060
	Q9	-0.085	±0.021	±0.080
	Q10	-0.120	±0.035	±0.144

M1.5 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.005	±0.024
	Q6	-0.020	±0.008	±0.032
	Q7	-0.040	±0.008	±0.042
	Q8	-0.066	±0.015	±0.060
	Q9	-0.080	±0.020	±0.090
	Q10	-0.120	±0.034	±0.140

M2 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.005	±0.025
	Q6	-0.020	±0.008	±0.035
	Q7	-0.040	±0.008	±0.042
	Q8	-0.066	±0.016	±0.060
	Q9	-0.085	±0.021	±0.090
	Q10	-0.120	±0.035	±0.144

M1.5 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.009	±0.036
	Q7	-0.040	±0.009	±0.042
	Q8	-0.088	±0.016	±0.072
	Q9	-0.130	±0.024	±0.090
	Q10	-0.180	±0.037	±0.148

M2 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.027
	Q6	-0.020	±0.008	±0.036
	Q7	-0.040	±0.008	±0.044
	Q8	-0.095	±0.016	±0.072
	Q9	-0.130	±0.025	±0.104
	Q10	-0.180	±0.038	±0.160

M1.5 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.009	±0.038
	Q7	-0.040	±0.009	±0.044
	Q8	-0.088	±0.016	±0.072
	Q9	-0.130	±0.024	±0.104
	Q10	-0.180	±0.038	±0.160

M2 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.027
	Q6	-0.020	±0.008	±0.038
	Q7	-0.040	±0.008	±0.046
	Q8	-0.100	±0.016	±0.072
	Q9	-0.135	±0.023	±0.104
	Q10	-0.180	±0.038	±0.160

	Quality Classes	Quality Tolerances	Pitch Error
--	-----------------	--------------------	-------------

	Quality Classes	Quality Tolerances	Pitch Error
--	-----------------	--------------------	-------------

M3 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.006	±0.022
	Q6	-0.020	±0.009	±0.035
	Q7	-0.040	±0.009	±0.037
	Q8	-0.066	±0.016	±0.060
	Q9	-0.085	±0.024	±0.090
	Q10	-0.120	±0.036	±0.160

M4 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.026
	Q6	-0.020	±0.009	±0.035
	Q7	-0.040	±0.009	±0.040
	Q8	-0.066	±0.016	±0.060
	Q9	-0.085	±0.024	±0.090
	Q10	-0.120	±0.040	±0.170

M3 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.006	±0.025
	Q6	-0.020	±0.009	±0.035
	Q7	-0.040	±0.009	±0.044
	Q8	-0.066	±0.016	±0.066
	Q9	-0.085	±0.024	±0.100
	Q10	-0.120	±0.036	±0.160

M4 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.026
	Q6	-0.020	±0.009	±0.035
	Q7	-0.040	±0.009	±0.044
	Q8	-0.066	±0.016	±0.066
	Q9	-0.085	±0.024	±0.110
	Q10	-0.120	±0.040	±0.170

M3 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.030
	Q6	-0.020	±0.009	±0.036
	Q7	-0.040	±0.009	±0.050
	Q8	-0.095	±0.016	±0.072
	Q9	-0.130	±0.024	±0.104
	Q10	-0.180	±0.041	±0.167

M4 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.032
	Q6	-0.020	±0.010	±0.040
	Q7	-0.040	±0.010	±0.056
	Q8	-0.095	±0.018	±0.072
	Q9	-0.130	±0.025	±0.120
	Q10	-0.180	±0.045	±0.180

M3 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.030
	Q6	-0.020	±0.010	±0.042
	Q7	-0.040	±0.010	±0.052
	Q8	-0.095	±0.018	±0.078
	Q9	-0.130	±0.026	±0.112
	Q10	-0.180	±0.044	±0.180

M4 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.032
	Q6	-0.020	±0.010	±0.044
	Q7	-0.040	±0.010	±0.056
	Q8	-0.095	±0.019	±0.078
	Q9	-0.130	±0.026	±0.120
	Q10	-0.180	±0.045	±0.180

Quality Classes	Quality Tolerances	Pitch Error
-----------------	--------------------	-------------

Quality Classes	Quality Tolerances	Pitch Error
-----------------	--------------------	-------------

M5 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.026
	Q6	-0.020	±0.009	±0.035
	Q7	-0.040	±0.009	±0.040
	Q8	-0.066	±0.018	±0.071
	Q9	-0.085	±0.026	±0.100
	Q10	-0.120	±0.042	±0.170

M6 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.026
	Q6	-0.020	±0.010	±0.035
	Q7	-0.040	±0.010	±0.040
	Q8	-0.066	±0.018	±0.071
	Q9	-0.085	±0.026	±0.105
	Q10	-0.120	±0.042	±0.170

M5 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.028
	Q6	-0.020	±0.010	±0.035
	Q7	-0.040	±0.010	±0.044
	Q8	-0.066	±0.018	±0.078
	Q9	-0.085	±0.026	±0.110
	Q10	-0.120	±0.042	±0.170

M6 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.007	±0.028
	Q6	-0.020	±0.010	±0.040
	Q7	-0.040	±0.010	±0.044
	Q8	-0.066	±0.018	±0.078
	Q9	-0.085	±0.026	±0.110
	Q10	-0.120	±0.042	±0.170

M5 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.010	±0.040
	Q7	-0.040	±0.010	±0.050
	Q8	-0.095	±0.019	±0.080
	Q9	-0.130	±0.028	±0.120
	Q10	-0.180	±0.045	±0.180

M6 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.010	±0.040
	Q7	-0.040	±0.010	±0.052
	Q8	-0.095	±0.019	±0.080
	Q9	-0.130	±0.028	±0.120
	Q10	-0.180	±0.045	±0.180

M5 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.010	±0.044
	Q7	-0.040	±0.010	±0.054
	Q8	-0.095	±0.019	±0.090
	Q9	-0.130	±0.028	±0.120
	Q10	-0.180	±0.045	±0.190

M6 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
	Q6	-0.020	±0.010	±0.044
	Q7	-0.040	±0.010	±0.054
	Q8	-0.095	±0.019	±0.090
	Q9	-0.130	±0.028	±0.120
	Q10	-0.180	±0.045	±0.190

	Quality Classes	Quality Tolerances	Pitch Error
--	-----------------	--------------------	-------------

M8 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.026
Q6	-0.020	±0.010	±0.035	
Q7	-0.040	±0.010	±0.042	
Q8	-0.066	±0.021	±0.081	
Q9	-0.085	±0.028	±0.110	
Q10	-0.120	±0.048	±0.180	

	Quality Classes	Quality Tolerances	Pitch Error
--	-----------------	--------------------	-------------

M10 L500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.026
Q6	-0.020	±0.016	±0.026	
Q7	-0.040	±0.016	±0.042	
Q8	-0.066	±0.022	±0.060	
Q9	-0.085	±0.030	±0.110	
Q10	-0.120	±0.048	±0.180	


M8 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.030
Q6	-0.020	±0.011	±0.040	
Q7	-0.040	±0.011	±0.044	
Q8	-0.066	±0.021	±0.084	
Q9	-0.085	±0.028	±0.110	
Q10	-0.120	±0.048	±0.180	

M10 L1000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	-0.015	±0.008	±0.030
Q6	-0.036	±0.016	±0.034	
Q7	-0.040	±0.016	±0.043	
Q8	-0.066	±0.022	±0.060	
Q9	-0.085	±0.030	±0.110	
Q10	-0.120	±0.048	±0.180	

M8 L1500	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
Q6	-0.020	±0.011	±0.041	
Q7	-0.040	±0.011	±0.051	
Q8	-0.095	±0.021	±0.090	
Q9	-0.130	±0.031	±0.130	
Q10	-0.180	±0.050	±0.200	

M8 L2000	Quality Classes	Tooth Thickness Error (mm)	Single Pitch Error (mm)	Total Pitch Error (mm)
	Q5	N/A	N/A	N/A
Q6	-0.020	±0.011	±0.044	
Q7	-0.040	±0.011	±0.054	
Q8	-0.095	±0.021	±0.095	
Q9	-0.130	±0.031	±0.130	
Q10	-0.180	±0.050	±0.200	






Q5 - C45

Specifications

Quality	Din5	Heat - Treatment	Teeth Induction Hardened
Material	C45 (Carbon Steel)	Hardness	HRC 50-55
Helical Angle	19° 31' 42" Right Hand	Surface	Ground Surfaces and Ground Teeth
Pressure Angle	20°		



Dimensions (M: Module • Pt: Tooth Pitch • Z: Number of Teeth)


Item Code	M	L	L2	Pt	Z	A	B	B0	C	D	N° of Holes	B1	G1	G2	F	C0	E	G3	KG
SHGH1.50505	1.5	500	6	5.0000	100	17	17	15.5	62.50	125	4	8	6	9.5	7	31.7	436.6	5.7	1.3
SHGH1.51005	1.5	1000	6	5.0000	200	17	17	15.5	62.50	125	8	8	6	9.5	7	31.7	936.6	5.7	2.6
SHGH020505	2	500	8.5	6.6666	75	24	24	22.0	62.50	125	4	8	7	11.0	7	31.7	436.6	5.7	2.1
SHGH021005	2	1000	8.5	6.6666	150	24	24	22.0	62.50	125	8	8	7	11.0	7	31.7	936.6	5.7	4.1
SHGH021505	2	1500	8.5	6.6666	225	24	24	22.0	62.50	125	12	8	7	11.0	7	31.7	1436.6	5.7	6.1
SHGH022005	2	2000	8.5	6.6666	300	24	24	22.0	62.50	125	16	8	7	11.0	7	31.7	1936.6	5.7	8.1
SHGH030505	3	500	10.3	10.0000	50	29	29	26.0	62.50	125	4	9	10	15.0	9	35.0	430.0	7.7	2.9
SHGH031005	3	1000	10.3	10.0000	100	29	29	26.0	62.50	125	8	9	10	15.0	9	35.0	930.0	7.7	5.7
SHGH031505	3	1500	10.3	10.0000	150	29	29	26.0	62.50	125	12	9	10	15.0	9	35.0	1430.0	7.7	8.5
SHGH032005	3	2000	10.3	10.0000	200	29	29	26.0	62.50	125	16	9	10	15.0	9	35.0	1930.0	7.7	11.4
SHGH040505	4	506.67	13.8	13.3333	38	39	39	35.0	62.50	125	4	12	10	15.0	9	33.3	433.4	7.7	5.3
SHGH041005	4	1000	13.8	13.3333	75	39	39	35.0	62.50	125	8	12	10	15.0	9	33.3	933.4	7.7	10.4
SHGH041505	4	1506.67	13.8	13.3333	113	39	39	35.0	62.50	125	12	12	10	15.0	9	33.3	1440.1	11.7	15.7
SHGH042005	4	2000	13.8	13.3333	150	39	39	35.0	62.50	125	16	12	10	15.0	9	33.3	1933.4	11.7	20.8
SHGH050505	5	500	17.4	16.6666	30	49	39	34.0	62.50	125	4	12	14	20.0	13	37.5	425.0	11.7	6.1
SHGH051005	5	1000	17.4	16.6666	60	49	39	34.0	62.50	125	8	12	14	20.0	13	37.5	925.0	11.7	12.3
SHGH060505	6	500	20.9	20.0000	25	59	49	43.0	62.50	125	4	16	18	26.0	17	37.5	425.0	15.7	9.1
SHGH061005	6	1000	20.9	20.0000	50	59	49	43.0	62.50	125	8	16	18	26.0	17	37.5	925.0	15.7	18.4
SHGH080505	8	500	28	26.6667	18	79	79	71.0	60.00	120	4	25	22	33.0	21	120.0	240.0	19.7	20.0
SHGH081005	8	1000	28	26.6667	36	79	79	71.0	60.00	120	8	25	22	33.0	21	120.0	720.0	19.7	40.2
SHGH100505	10	500	35.11	33.3333	15	99	99	89.0	62.50	125	4	32	33	48.0	32	125.0	250.0	19.7	35.0
SHGH101005	10	1000	35.11	33.3333	30	99	99	89.0	62.50	125	8	32	33	48.0	32	125.0	750.0	19.7	68.7

Notes: Available Material on rack- Carbon Steel/42CrMo4/Stainless/Aluminum alloy.

Q10 - C45

Specifications

Quality	Din10	Heat - Treatment	Teeth Induction Hardened
Material	C45 (Carbon Steel)	Hardness	HRC 50-55
Helical Angle	19° 31' 42" Right Hand	Surface	Milled Surfaces and Milled Teeth
Pressure Angle	20°	Finishing	Options




Dimensions (M: Module • Pt: Tooth Pitch • Z: Number of Teeth)

Item Code	M	L	L2	Pt	Z	A	B	B0	C	D	N° of Holes	B1	G1	G2	F	C0	E	G3	KG
SHFH1.50510	1.5	500	6	5.0000	100	17	17	15.5	62.50	125	4	8	6	9.5	7	31.7	436.6	5.7	1.4
SHFH1.51010	1.5	1000	6	5.0000	200	17	17	15.5	62.50	125	8	8	6	9.5	7	31.7	936.6	5.7	2.8
SHFH1.51510	1.5	1500	6	5.0000	300	17	17	15.5	62.50	125	12	8	6	9.5	7	31.7	1436.6	5.7	4.3
SHFH1.52010	1.5	2000	6	5.0000	400	17	17	15.5	62.50	125	16	8	6	9.5	7	31.7	1936.6	5.7	5.4
SHFH020510	2	500	8.5	6.6666	75	24	24	22.0	62.50	125	4	8	7	11.0	7	31.7	436.6	5.7	2.2
SHFH021010	2	1000	8.5	6.6666	150	24	24	22.0	62.50	125	8	8	7	11.0	7	31.7	936.6	5.7	4.4
SHFH021510	2	1500	8.5	6.6666	225	24	24	22.0	62.50	125	12	8	7	11.0	7	31.7	1436.6	5.7	6.6
SHFH022010	2	2000	8.5	6.6666	300	24	24	22.0	62.50	125	16	8	7	11.0	7	31.7	1936.6	5.7	8.8
SHFH030510	3	500	10.3	10.0000	50	29	29	26.0	62.50	125	4	9	10	15.0	9	35.0	430.0	7.7	3.1
SHFH031010	3	1000	10.3	10.0000	100	29	29	26.0	62.50	125	8	9	10	15.0	9	35.0	930.0	7.7	6.1
SHFH031510	3	1500	10.3	10.0000	150	29	29	26.0	62.50	125	12	9	10	15.0	9	35.0	1430.0	7.7	9.2
SHFH032010	3	2000	10.3	10.0000	200	29	29	26.0	62.50	125	16	9	10	15.0	9	35.0	1930.0	7.7	12.2
SHFH040510	4	506.67	13.8	13.3333	38	39	39	35.0	62.50	125	4	12	10	15.0	9	33.3	433.4	7.7	5.5
SHFH041010	4	1000	13.8	13.3333	75	39	39	35.0	62.50	125	8	12	10	15.0	9	33.3	933.4	7.7	11.0
SHFH041510	4	1506.67	13.8	13.3333	113	39	39	35.0	62.50	125	12	12	10	15.0	9	33.3	1440.1	7.7	16.1
SHFH042010	4	2000	13.8	13.3333	150	39	39	35.0	62.50	125	16	12	10	15.0	9	33.3	1933.4	7.7	22.0
SHFH050509	5	500	17.4	16.6666	30	49	49	34.0	62.50	125	4	12	14	20.0	13	37.5	425.0	11.7	6.5
SHFH051009	5	1000	17.4	16.6666	60	49	49	34.0	62.50	125	8	12	14	20.0	13	37.5	925.0	11.7	13.0
SHFH051509	5	1500	17.4	16.6666	90	49	49	34.0	62.50	125	12	12	14	20.0	13	37.5	1425.0	11.7	19.5
SHFH052009	5	2000	17.4	16.6666	120	49	49	34.0	62.50	125	16	12	14	20.0	13	37.5	1925.0	11.7	26.0
SHFH060510	6	500	20.9	20.0000	25	59	49	43.0	62.50	125	4	16	18	26.0	17	37.5	425.0	15.7	9.5
SHFH061010	6	1000	20.9	20.0000	50	59	49	43.0	62.50	125	8	16	18	26.0	17	37.5	925.0	15.7	19.2
SHFH061510	6	1500	20.9	20.0000	75	59	49	43.0	62.50	125	12	16	18	26.0	17	37.5	1425.0	15.7	28.7
SHFH062010	6	2000	20.9	20.0000	100	59	49	43.0	62.50	125	16	16	18	26.0	17	37.5	1925.0	15.7	38.5
SHFH080510	8	480	28	26.6667	18	79	79	71.0	60.00	120	4	25	22	33.0	21	120.0	240.0	19.7	20.0
SHFH081010	8	960	28	26.6667	36	79	79	71.0	60.00	120	8	25	22	33.0	21	120.0	720.0	19.7	40.2
SHFH081510	8	1440	28	26.6667	54	79	79	71.0	60.00	120	12	25	22	33.0	21	120.0	1200.0	19.7	59.6
SHFH082010	8	1920	28	26.6667	72	79	79	71.0	60.00	120	16	25	22	33.0	21	120.0	1680.0	19.7	80.8
SHFH100510	10	500	35.11	33.3333	15	99	99	89.0	62.50	125	4	32	33	48.0	32	125.0	250.0	19.7	35.0
SHFH101010	10	1000	35.11	33.3333	30	99	99	89.0	62.50	125	8	32	33	48.0	32	125.0	750.0	19.7	68.7


Notes: Available Material on rack- Carbon Steel/42CrMo4/Stainless/Aluminum alloy.





	Opposite Tooth Gauge
Material	C45
Surface	Ground Teeth


Helical Tooth Gauge



Dimensions (Helical Tooth System: 19° 31' 42" Left Hand)

Item Code	Module	L	H	B	Z	fp	FP
SHG02-GAUGE	2	150	24	24	22	0.004	0.015
SHG03-GAUGE	3	150	29	29	15	0.004	0.015
SHG04-GAUGE	4	150	39	39	11	0.003	0.010
SHG05-GAUGE	5	150	49	39	9	0.003	0.010
SHG06-GAUGE	6	150	59	49	7	0.003	0.010

Straight Tooth Gauge



Dimensions

Item Code	Module	L	H	B	Z	fp	FP
SSG02-GAUGE	2	150	24	24	22	0.004	0.015
SSG03-GAUGE	3	150	29	29	15	0.004	0.015
SSG04-GAUGE	4	150	39	39	11	0.003	0.010
SSG05-GAUGE	5	150	49	39	9	0.003	0.010
SSG06-GAUGE	6	150	59	49	7	0.003	0.010


Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

Q5 - 16CrMo4

Ground Pinion

Specifications

Quality	5e24	Heat - Treatment	Case Hardening
Material	16CrMo4	Hardness	HRC 55-60
Helical Tooth	19° 31' 42" Left Hand	Surface	Ground



Dimensions

Item Code	M	Z	Da	Dp	Kw	Kd	A _(H6)	B	L	Kd
HGK1.51610B65L	1.5	16	28.46	25.46	4	11.5	10	28	65	20
HGK1.51815B65L	1.5	18	31.64	28.64	5	17.3	15	28	65	22
HGK1.52015B65L	1.5	20	34.83	31.83	5	17.3	15	28	65	25
HGK1.52420B65L	1.5	24	41.19	38.19	6	22.8	20	28	65	32
HGK1.54040B65L	1.5	40	66.66	63.66	12	43.3	40	28	65	58
HGK021615B65L	2	16	37.95	33.95	5	17.3	15	28	65	25
HGK021815B65L	2	18	42.20	38.20	5	17.3	15	28	65	30
HGK022122B56L	2	21	48.56	44.56	6	24.8	22	26	56	36
HGK022225B65L	2	22	50.69	46.69	8	28.3	25	28	65	36
HGK022425B65L	2	24	54.93	50.93	8	28.3	25	28	65	36
HGK023025B65L	2	30	67.66	63.66	8	28.3	25	28	65	36
HGK024040B65L	2	40	88.88	84.88	12	43.3	40	28	65	62
HGK032020B65L	3	20	69.66	63.66	6	22.8	20	28	65	30
HGK032225B65L	3	22	76.03	70.03	8	28.3	25	28	65	36
HGK032425B65L	3	24	82.39	76.39	8	28.3	25	28	65	36
HGK034040B65L	3	40	133.32	127.32	12	43.3	40	28	65	62
HGK042035B75L	4	20	92.88	84.88	10	38.3	35	40	75	55
HGK042535B75L	4	25	114.10	106.10	10	38.3	35	40	75	55
HGK043035B75L	4	30	135.32	127.32	10	38.3	35	40	75	55
HGK043235B75L	4	32	143.81	135.81	10	38.3	35	40	75	55
HGK052045B75L	5	20	116.10	106.10	14	48.8	45	50	75	68
HGK052445B75L	5	24	137.32	127.32	14	48.8	45	50	75	68
HGK052545B75L	5	25	142.63	132.63	14	48.8	45	50	75	68
HGK053045B75L	5	30	169.15	159.15	14	48.8	45	50	75	68
HGK062055B120L	6	20	139.32	127.32	16	59.3	55	60	120	80
HGK062155B120L	6	21	145.69	133.69	16	59.3	55	60	120	80
HGK062455B120L	6	24	164.79	152.79	16	59.3	55	60	120	80
HGK062555B120L	6	25	171.15	159.15	16	59.3	55	60	120	80
HGK063055B120L	6	30	202.99	190.99	16	59.3	55	60	120	80
HGK082075B145L	8	20	185.77	169.77	20	79.9	75	80	145	110
HGK102085B165L	10	20	232.21	212.21	22	90.4	85	100	165	125


Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

Q5 - 16CrMo4

Flanged Pinion

Specifications

Quality	5e24	Heat - Treatment	Case Hardening
Material	16CrMo4	Hardness	HRC 55-60
Helical Tooth	19° 31' 42" Left Hand	Surface	Ground
Pressure Angle	20°		



Dimensions

Item Code	Model	M	Z	X	De	Dp	Dm(h6)	A	H1	H2	DF	Df	DC	HC
HGFA022615B29L	A	2	26	0.4065	60.60	56.80	20.0	15.0	29.0	26	31.5	5.5	10	12
HGFA022715B33.5L	A	2	27	0.0000	61.29	57.30	20.0	15.0	33.5	30	31.5	5.5	10	11
HGFA022915B29L	A	2	29	0.4150	67.00	63.20	20.0	15.0	29.0	26	31.5	5.5	10	12
HGFA023320B30L	A	2	33	0.3928	75.30	71.60	31.5	20.0	30.0	26	50.0	6.6	11	14
HGFA023515B29L	A	2	35	0.3819	79.60	75.80	20.0	15.0	29.0	26	31.5	5.5	10	12
HGFA023620B34L	A	2	36	0.0000	80.39	76.40	31.5	20.0	34.0	30	50.0	6.6	11	8
HGFA023720B30L	A	2	37	0.4209	84.00	80.20	31.5	20.0	30.0	26	50.0	6.6	11	14
HGFB023720B30L	B	2	37	0.4209	84.00	80.20	31.5	20.0	30.0	26	50.0	6.6	11	14
HGFC024031.5B30L	C	2	40	0.3792	90.20	86.40	40.0	31.5	30.0	26	63.0	6.6	11	14
HGFC024531.5B30L	C	2	45	0.3267	100.60	96.80	40.0	31.5	30.0	26	63.0	6.6	11	14
HGFA033120B35.5L	A	3	31	0.3540	106.60	100.80	31.5	20.0	35.5	31	50.0	6.6	11	9
HGFB033540B35L	B	3	35	0.3652	119.40	113.60	50.0	40.0	35.0	31	80.0	9.0	15	11
HGFB034040B35L	B	3	40	0.3792	135.40	129.60	50.0	40.0	35.0	31	80.0	9.0	15	11
HGFC033020B39L	C	3	30	0.0000	101.49	95.49	40.0	20.0	39.0	35	63.0	6.6	11	10
HGFB043040B49L	B	4	30	0.0000	135.32	127.32	50.0	40.0	49.0	45	80.0	9.0	15	11
HGFB053660B61L	B	5	36	0.0000	200.98	190.99	80.0	60.0	61.0	55	125.0	11.0	18	13


Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

Q10 - C45

Milled Pinion

Specifications

Quality	10e25	Heat - Treatment	Induction Hardening
Material	C45	Hardness	HRC 50-55
Helical Tooth	19° 31' 42" Left Hand	Surface	Milled Teeth, Black Oxide



Dimensions

Item Code	M	Z	Da	Dp	Kw	Kd	A(H7)	B	L	Kd
HMK1.51610B65L	1.5	16	28.46	25.46	4	11.5	10	28	65	20
HMK1.51815B65L	1.5	18	31.64	28.64	5	17.3	15	28	65	22
HMK1.52015B65L	1.5	20	34.83	31.83	5	17.3	15	28	65	25
HMK1.52420B65L	1.5	24	41.19	38.19	6	22.8	20	28	65	32
HMK1.54040B65L	1.5	30	50.74	47.74	8	28.3	25	28	65	40
HMK021615B65L	1.5	40	66.66	63.66	12	43.3	40	28	65	58
HMK021815B65L	2	16	37.95	33.95	5	17.3	15	28	65	25
HMK022122B56L	2	18	42.20	38.20	5	17.3	15	28	65	30
HMK022225B65L	2	20	46.44	42.44	6	22.8	20	28	65	30
HMK022425B65L	2	22	50.69	46.69	8	28.3	25	28	65	36
HMK023025B65L	2	24	54.93	50.93	8	28.3	25	28	65	36
HMK024040B65L	2	30	67.66	63.66	8	28.3	25	28	65	36
HMK032020B65L	2	40	88.88	84.88	12	43.3	40	28	65	62
HMK032225B65L	3	20	69.66	63.66	6	22.8	20	28	65	30
HMK032425B65L	3	22	76.03	70.03	8	28.3	25	28	65	36
HMK034040B65L	3	24	82.39	76.39	8	28.3	25	28	65	36
HMK042035B75L	3	40	133.32	127.32	12	43.3	40	28	65	62
HMK042535B75L	4	20	92.88	84.88	10	38.3	35	40	75	55
HMK043035B75L	4	25	114.10	106.10	10	38.3	35	40	75	55
HMK043235B75L	4	30	135.32	127.32	10	38.3	35	40	75	55
HMK052045B75L	4	32	143.81	135.81	10	38.3	35	40	75	55
HMK052445B75L	5	20	116.10	106.10	14	48.8	45	50	75	68
HMK052545B75L	5	24	137.32	127.32	14	48.8	45	50	75	68
HMK053045B75L	5	25	142.63	132.63	14	48.8	45	50	75	68
HMK062055B120L	5	30	169.15	159.15	14	48.8	45	50	75	68
HMK062155B120L	6	20	139.32	127.32	16	59.3	55	60	120	80
HMK062455B120L	6	21	145.69	133.69	16	59.3	55	60	120	80
HMK062555B120L	6	24	164.79	152.79	16	59.3	55	60	120	80
HMK063055B120L	6	25	171.15	159.15	16	59.3	55	60	120	80
HMK082075B145L	6	30	202.99	190.99	16	59.3	55	60	120	80
HMK102085B165L	8	20	185.77	169.77	20	79.9	75	80	145	110
	10	20	232.21	212.21	22	90.4	85	100	165	125


Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

Q5 - 16CrMo4

Ground Pinion

Specifications

Quality	5e24	Heat - Treatment	Case Hardening
Material	16CrMo4	Hardness	HRC 55-60
Pressure Angle	20°	Surface	Ground Teeth



Dimensions

Item Code	M	Z	Da	Dp	Kw	Kd	A _(H6)	B	L	Kd
SGK1.51610B65L	1.5	16	27	24	4	11.5	10	28	65	20
SGK1.51815B65L	1.5	18	30	27	5	17.3	15	28	65	22
SGK1.52015B65L	1.5	20	33	30	5	17.3	15	28	65	25
SGK1.52420B65L	1.5	24	39	36	6	22.8	20	28	65	32
SGK1.54040B65L	1.5	30	48	45	8	28.3	25	28	65	40
SGK021615B65L	1.5	40	63	60	12	43.3	40	28	65	58
SGK021815B65L	2	16	36	32	5	17.3	15	28	65	25
SGK022122B56L	2	18	40	36	5	17.3	15	28	65	30
SGK022225B65L	2	20	44	40	6	22.8	20	28	65	30
SGK022425B65L	2	22	48	44	8	28.3	25	28	65	36
SGK023025B65L	2	24	52	48	8	28.3	25	28	65	36
SGK024040B65L	2	30	64	60	8	28.3	25	28	65	36
SGK032020B65L	2	40	84	80	12	43.3	40	28	65	62
SGK032225B65L	3	20	66	60	6	22.8	20	28	65	30
SGK032425B65L	3	22	72	66	8	28.3	25	28	65	36
SGK034040B65L	3	24	78	72	8	28.3	25	28	65	36
SGK042035B75L	3	40	126	120	12	43.3	40	28	65	62
SGK042535B75L	4	20	88	80	10	38.3	35	40	75	55
SGK043035B75L	4	25	108	100	10	38.3	35	40	75	55
SGK043235B75L	4	30	128	120	10	38.3	35	40	75	55
SGK052045B75L	4	32	136	128	10	38.3	35	40	75	55
SGK052445B75L	5	20	110	100	14	48.8	45	50	75	68
SGK052545B75L	5	24	130	120	14	48.8	45	50	75	68
SGK053045B75L	5	25	135	125	14	48.8	45	50	75	68
SGK062055B120L	5	30	160	150	14	48.8	45	50	75	68
SGK062155B120L	6	20	132	120	16	59.3	55	60	120	80
SGK062455B120L	6	21	138	126	16	59.3	55	60	120	80
SGK062555B120L	6	24	156	144	16	59.3	55	60	120	80
SGK063055B120L	6	25	162	150	16	59.3	55	60	120	80
SGK082075B145L	6	30	192	180	16	59.3	55	60	120	80
SGK102085B165L	8	20	176	160	20	79.9	75	80	145	110
	10	20	220	200	22	90.4	85	100	165	125


Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

Q10 - C45

Milled Pinion

Specifications

Quality	10e25	Heat - Treatment	Induction Hardening
Material	C45	Hardness	HRC 50-55
Pressure Angle	20°	Surface	Milled Teeth



Dimensions

Item Code	M	Z	Da	Dp	Kw	Kd	A _(H6)	B	L	Kd
SMK1.51610B65L	1.5	16	27	24	4	11.5	10	28	65	20
SMK1.51815B65L	1.5	18	30	27	5	17.3	15	28	65	22
SMK1.52015B65L	1.5	20	33	30	5	17.3	15	28	65	25
SMK1.52420B65L	1.5	24	39	36	6	22.8	20	28	65	32
SMK1.54040B65L	1.5	30	48	45	8	28.3	25	28	65	40
SMK021615B65L	1.5	40	63	60	12	43.3	40	28	65	58
SMK021815B65L	2	16	36	32	5	17.3	15	28	65	25
SMK022122B56L	2	18	40	36	5	17.3	15	28	65	30
SMK022225B65L	2	20	44	40	6	22.8	20	28	65	30
SMK022425B65L	2	22	48	44	8	28.3	25	28	65	36
SMK023025B65L	2	24	52	48	8	28.3	25	28	65	36
SMK024040B65L	2	30	64	60	8	28.3	25	28	65	36
SMK032020B65L	2	40	84	80	12	43.3	40	28	65	62
SMK032225B65L	3	20	66	60	6	22.8	20	28	65	30
SMK032425B65L	3	22	72	66	8	28.3	25	28	65	36
SMK034040B65L	3	24	78	72	8	28.3	25	28	65	36
SMK042035B75L	3	40	126	120	12	43.3	40	28	65	62
SMK042535B75L	4	20	88	80	10	38.3	35	40	75	55
SMK043035B75L	4	25	108	100	10	38.3	35	40	75	55
SMK043235B75L	4	30	128	120	10	38.3	35	40	75	55
SMK052045B75L	4	32	136	128	10	38.3	35	40	75	55
SMK052445B75L	5	20	110	100	14	48.8	45	50	75	68
SMK052545B75L	5	24	130	120	14	48.8	45	50	75	68
SMK053045B75L	5	25	135	125	14	48.8	45	50	75	68
SMK062055B120L	5	30	160	150	14	48.8	45	50	75	68
SMK062155B120L	6	20	132	120	16	59.3	55	60	120	80
SMK062455B120L	6	21	138	126	16	59.3	55	60	120	80
SMK062555B120L	6	24	156	144	16	59.3	55	60	120	80
SMK063055B120L	6	25	162	150	16	59.3	55	60	120	80
SMK082075B145L	6	30	192	180	16	59.3	55	60	120	80
SMK102085B165L	8	20	176	160	20	79.9	75	80	145	110
	10	20	220	200	22	90.4	85	100	165	125

Notes: Available Material on pinion gear- Carbon Steel/16CrMn4/42CrMo4/Stainless/Aluminum alloy.
Any pinion gears are customizable.

KA
H
E



K.H. KAI HE MACHINERY CO., LTD

📍 No. 327, Ganxi Rd. Wufeng Dist., Taichung City 41354, Taiwan

☎ TEL: +886-4-2339-5817 📠 FAX: +886-4-2339-2308

✉ E-mail: sales@kh-rack.com



www.kh-rack.com